

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Deko-Light

Supplier's address: Product Management, Deko-Light Elektronik Vertriebs GmbH, Auf der Hub 2, D-76307 Karlsbad, DE

Model identifier: 730470

Type of light source:

| | | | |
|---|------------------|---------------------------------|------|
| Lighting technology used: | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | other electrical | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | Nein |
| Colour-tuneable light source: | Nein | Envelope: | - |
| High luminance light source: | Nein | | |
| Anti-glare shield: | Nein | Dimmable: | No |

Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

General product parameters:

| | | | |
|--|--------------------------|--|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 3 | Energy efficiency class | G |
| Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 146 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P_{on}), expressed in W | 2,4 | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer dimensions | Height | Spectral power distribution in the | See image in last page |
| | Width | | |
| | | | 55 |

| | | | | |
|---|-------|------|--|----------------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) | Depth | 55 | range 250 nm to 800 nm, at full-load | |
| Claim of equivalent power ^(a) | | - | If yes, equivalent power (W) | - |
| | | | Chromaticity coordinates (x and y) | 0,434 0,403 |
| Parameters for directional light sources: | | | | |
| Peak luminous intensity (cd) | | 451 | Beam angle in degrees, or the range of beam angles that can be set | 32 |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | | 7 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,70 | | |

(a) '-': not applicable;

(b) '-': not applicable;

